

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY,

THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 1, 4, 10, AND 11

IN

TOWNSHIP 37 SOUTH, RANGE 17 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jeremy D. Davis
Cadastral Surveyor

under the supervision of

Ronald K. Baugh
Supervisory Cadastral Surveyor

Under special instructions dated *April 27, 2007*, approved *April 27, 2007*, which provided for the surveys included under Group Number *1048*, and assignment instructions dated *April 27, 2007*, and reassignment instructions dated *July 20, 2007*.

Survey commenced *May 16, 2007*
Survey completed *July 30, 2007*

INDEX DIAGRAM

Township 37 South, Range 17 West

14 13 12 6	12 11 5 23 23	10 9 4 22 22 20	9 8 3 19 21 18	7 6 2 16 18 15	4 3 1 3 15 3
7	8	9 20 19	10 17 27 17	11 14 14	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 1.....Page 24
The Subdivision of Section 4.....Page 26
The Subdivision of Section 10.....Page 27
The Subdivision of Section 11.....Page 29

TOWNSHIP 37 SOUTH, RANGE 17 WEST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the east boundary, the north boundary, a portion of the subdivisional lines, and the subdivision of sections 1, 4, 10, and 11, in T. 37 S., R. 17 W., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by
SOUTH BOUNDARY		
All	T.C. Bailey	1881
All	R. Gentry & H.D. Heist	1911 R. Gentry & H.D. Heist 1911
EAST BOUNDARY		
All	T.C. Bailey	1881
Portion		R. Gentry & H.D. Heist 1911
WEST BOUNDARY		
All	T.C. Bailey	1881
Portion		R. Gentry & H.D. Heist 1911
NORTH BOUNDARY		
All	T.C. Bailey	1881
All		M.H. Dalley 1899
Portion		J.D. Davis, R.K. Baugh 2007 (Concurrently)
SUBDIVISION		
Portion	T.C. Bailey	1881
Portion	R. Gentry & H.D. Heist	1911 R. Gentry & H.D. Heist 1911
Portion		R.K. Baugh 2006
HOMESTEAD ENTRIES		
Number 38	J.C. Brown	1913
Number 39	J.C. Brown	1913
Number 71	A.M. Woodbury	1913

COUNTY SURVEYS

A survey was executed by Howard G. Stevens, Washington County Surveyor, with a Washington County area reference plat for section 14, dated August 1973, on file at the Washington County Recorder's Office.

A survey was executed by Dean D. Holliday, L.S. 4666, with a Washington County area reference plat for section 12, dated June 1979, on file at the Washington County Recorder's Office.

PRIVATE SURVEYS

A survey was executed by Doug Grimshaw, L.S. 174457, with a record of survey plat for section 1, dated April 19, 1995, on record at the Washington County Recorder's Office.

TOWNSHIP 37 SOUTH, RANGE 17 WEST, SALT LAKE MERIDIAN, UTAH

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1048, dated April 27, 2007.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from National Geodetic Survey Station "BIG MOUNTAIN", with the published data as follows:

Latitude: 37°30'38.81714"N. Longitude: 113°39'25.24791"W.
NAD 1983 (1994).

The geographic position of the corner of 11, 12, 13, and 14, T. 37 S., R. 17 W., as determined by using RTK methods from indirect ties made to National Geodetic Survey Station "BIG MOUNTAIN" is as follows:

Latitude: 37°34'30.914" N. Longitude: 113°43'00.560" W.
N.A.D. 83 Network Accuracy = .305 meters at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Dependent Resurvey of a Portion of the East Boundary,
T. 37 S., R. 17 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by
T.C. Bailey in 1881.

Beginning at the section corner of sections 1, 6, 7, and 12, monumented with a Washington County survey monument, an iron pipe, 2 inches diameter, firmly set, 1 ft. below ground surface, with brass cap attached, with no visible markings. This monument is accepted as the best available evidence of the position of the original section corner.

An area reference plat, dated June 1979, is on file at the Washington County Recorder's Office.

Corner falls at the edge of an oiled road 21 ft. wide extending north and south, and 18 ft. from the south pole of a gate, bears north and south.

N. 0°11.8' W., between sections 1 and 6, along the east boundary of the township.

40.566 Point for the 1/4 section corner of sections 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 12 inches long, 2 1/2 inches diameter, 12 inches below road surface, with aluminum cap marked:

T37S
R17W R16W
1/4
S1|S6
2007

from which

A power pole, with a nail in it, bears N. 60° E., 29 links distance

Deposit two magnets enclosed in plastic cases at the base of the aluminum post.

Corner falls in oiled road 21 ft. wide, extending north and south.

81.132 The corner of Tps. 36 and 37 S., Rgs. 16 and 17 W., monumented with a Doug Grimshaw monument, a rebar, 5/8 inch diameter, firmly set, 1 inch below road surface, with yellow cap attached, with illegible marks. This monument is accepted as a

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Careful and faithful determination of the township corner position.

A record of survey plat, dated April 19, 1995, is on file at the Washington County Recorder's Office.

At the corner point

Set an aluminum post, 12 inches long, 2 1/2 inches diameter, 5 inches below road surface, with aluminum cap marked:

T36S
R17W R16W
S36|S31
S1|S6
T37S
2007

from which

A power pole, with a nail in it, bears N. 3°47.0' E., 94.2 links distance.

A power pole, with a nail in it, bears N. 29°47.8' E., 57.2 links distance.

A railroad tie, with a nail in it, bears N. 54°05.0' W., 73.6 links distance.

Deposit the rebar and cap at the base of the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls at the intersection of roads projecting north, south, east, and west.

The Dependent Resurvey of the North Boundary
T. 37 S., R. 17 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by T.C. Bailey in 1881,
and the Dependent Resurvey Executed by M.H. Dalley in 1899.

From the corner of Tps. 36 and 37 South, Rgs. 16 and 17 West.

N. 89°39.8' W., along the north boundary of section 1.

40.397

Point for the 1/4 section corner of section 36 only, T. 36 S., R. 17 W., at midpoint between the township corner and closing corner of section 35 and 36.

Set an aluminum post, 12 inches long, 2 1/2 inches diameter, 12 inches below road surface, with aluminum cap marked:

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

T36SR17W

1/4 S36

T37S

2007

from which

A railroad tie, with a nail in it, bears S. 28°57.1' W.,
71.0 links distance.

A railroad tie, with a nail in it, bears N. 77°32.2' W.,
42.5 links distance.

Deposit a magnet enclosed in a plastic case at the base of the
aluminum post.

Corner falls on north side of a dirt road, extending east and
west.

40.809

The 1/4 section corner of section 1 only, monumented with a
Doug Grimshaw monument, a rebar, 5/8 inch diameter, firmly
set, with cap missing. This corner is accepted as a careful
and faithful determination of the 1/4 section corner position.

A record of survey plat, dated April 19, 1995, is on file at
the Washington County Recorder's Office.

At the corner point

Set an aluminum post, 12 inches long, 2 1/2 inches diameter,
12 inches below road surface, with aluminum cap marked:

T36S1/4 S1

T37SR17W

2007

from which

A railroad tie, with a nail in it, bears S. 6°14.9' E.,
62.7 links distance.

A railroad tie, with a nail in it, bears N. 1°59.1' W.,
8.9 links distance.

Deposit the rebar at the base of the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the
aluminum post.

Corner falls on the north edge of a dirt road, extending east
and west.

S. 88°59.6' W., beginning new measurement.

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

- 20.524 The W 1/16 section corner of section 1 only, monumented with a Doug Grimshaw survey monument, a rebar, 5/8 inch diameter, firmly set, with yellow cap attached, with illegible marks. This corner is accepted as a careful and faithful determination of the W 1/16 section corner position.

A record of survey plat, dated April 19, 1995, is on file at the Washington County Recorder's Office.

At the corner point

Set an aluminum post, 12 inches long, 2 1/2 inches diameter, 12 inches below road surface, with aluminum cap marked:

W 1/16 S1
2007

from which

A railroad tie, with a nail in it, bears N. 44° E., 43 links distance.

Deposit the rebar and cap at the base of the aluminum post.

Deposit two magnets enclosed in plastic cases and rebar at the base of the aluminum post.

Corner falls at intersection of roads, projecting north, south, and east.

- 39.990 True point for the closing corner of sections 35 and 36 only, T. 36 S., R. 17 W., as described in the official record of the dependent resurvey of Township 36 South, Range 17 West, surveyed concurrently under this same Group No.

- 41.048 The corner of sections 1 and 2 only, monumented with a trachyte stone, 6x8x4 inches, firmly set, clearly marked 1 notch on east and 5 notches on west edges, and witnessed with a mound of stone to the east. (Record; 16x10x8 inches)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, with aluminum cap marked:

T36S
S2|S1
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post 1 ft. south of the aluminum post.

Corner falls on a gradual rocky northeast slope in sagebrush.

N. 89°52.5' W., along the north boundary of section 2.

39.270

Point for the 1/4 section corner of section 35 only, T. 36 S., R. 17 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36SR17W
1/4 S35
T37S
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls 10 ft. south of a fence line extending east and west, on a steep east slope in sagebrush and juniper growth.

40.373

The 1/4 section corner of section 2 only, monumented with a trachyte stone, 12x8x8 inches, firmly set, clearly marked 1/4 on north face. (Record; granite stone, 16x16x16 inches)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36S
1/4 S2
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls 10.7 ft. south of a fence line extending east and west.

N. 89°58.5' W., beginning new measurement

39.224

True point for the closing corner of sections 34 and 35 only, T. 36 S., R. 17 W., as described in the official record of the

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

dependent resurvey of Township 36 South, Range 17 West,
surveyed concurrently under this same Group No.

40.630

The corner of sections 2 and 3 only, monumented with a
trachyte stone, 14x10x5 inches, loosely set, clearly marked 2
notches on east edge, no other marks visible. (Record; 4
notches on west and 2 notches on east edges)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 2
inches in the ground, to solid rock, in a mound of stone, 3
ft. base, to top, with aluminum cap marked:

T36S
S3 | S2
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the
aluminum post.

Corner falls 1 ft. north of a fence line extending east and
west, on a gradual north slope in sagebrush and scattering
juniper growth

N. 88°55.7' W., along the north boundary of section 3.

38.907

Point for the 1/4 section corner of section 34 only, T. 36 S.,
R. 17 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
18 inches in the ground, to solid rock, in a mound of stone, 3
ft. base, to top, with aluminum cap marked:

T36SR17W
1/4 S34
T37S
2007

Deposit a magnet enclosed in a plastic case at the base of the
aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls in a fence line extending east and west, on a
gradual rocky west slope in juniper growth.

From this corner point, an unrecorded trachyte stone, 14x8x4
inches, firmly set, clearly marked 1/4, bears S. 13°05.9' W.,
21.0 links distance, and not utilized in the course of this
survey. Bury stone in place.

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS
40.049

The 1/4 section corner of section 3 only, monumented with a trachyte stone, 12x8x5 inches, firmly set, clearly marked 1/4 on west face, and witnessed with a mound of stone to the north. (Record; granite stone, marked 1/4 on north face.)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36S
1/4 S3
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post 1 ft. south of the aluminum post.

Corner falls 1 ft. north of a fence line extending east and west, on a gradual rocky west slope in sagebrush and juniper growth.

S. 89°05.7' W., beginning new measurement.

39.167 True point for the closing corner of sections 33 and 34, T. 36 S., R. 17 W., as described in the official record of the dependent resurvey of Township 36 South, Range 17 West, surveyed concurrently under this same Group No.

41.065 The corner of sections 3 and 4 only, monumented with a trachyte stone, 12x10x5 inches, firmly set, in a mound of stone, 3 ft. base, clearly marked 3 notches on west edge, no other marks visible. (Record; granite stone, 3 notches on east and west edges)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T36S
S4 | S3
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Raise a mound of stone, 4 ft. by 3 ft. base by 1 ft. high,
west of the aluminum post.

Corner falls 1 ft. south of a fence line extending east and
west, on a gradual north slope in sagebrush and scattering
juniper growth.

N. 89°19.7' W., along the north boundary of section 4.

38.496

Point for the 1/4 section corner of section 33 only, T. 36 S.,
R. 17 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
22 inches in the ground, to solid rock, in a mound of stone, 3
ft. base, to top, with aluminum cap marked:

T36SR17W

1/4 S33

T37S

2007

Deposit a magnet enclosed in a plastic case at the base of the
aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual east slope in june grass and old
burn.

From this corner point, an unrecorded trachyte stone, 12x12x4
inches, firmly set, clearly marked 1/4, and witnessed with a
mound of stone to the north, bears S. 2°13.0' W., 13.7 links
distance, not utilized in the course of this survey. Bury
stone in place.

40.553

The 1/4 section corner of section 4 only, monumented with a
granite stone, 16x10x8 inches, firmly set, clearly marked 1/4
on north face, and witnessed with a mound of stone to the
north.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
20 inches in the ground, to solid rock, in a mound of stone, 3
ft. base, to top, with aluminum cap marked:

T36S

1/4 S4

T37SR17W

2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the
aluminum post.

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel fence post alongside the aluminum post.

Corner falls 55.7 ft. north of a fence line extending east and west, on a gradual east slope in old burn.

N. 89°53.1' W., beginning new measurement.

38.333 Point for the closing corner of sections 32 and 33 only, T. 36 S., R. 17 W., as described in the official record of the dependent resurvey of Township 36 South, Range 17 West, surveyed concurrently under this same Group No.

40.768 The corner of sections 4 and 5 only, monumented with a trachyte stone, 10x6x6 inches, firmly set, clearly marked 4 notches on east and 2 notches on west edges, and witnessed with a mound of stone to the north. (Record; granite stone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36S
S5 | S4
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual north slope in sagebrush, bitterbrush, and scattering juniper growth.

N. 89°28.8' W., along the north boundary of section 5.

37.962 Point for the 1/4 section corner of section 32 only, T. 36 S., R. 17 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36SR17W
1/4 S32
T37S
2007

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a steep rocky north slope in juniper growth.

40.918

The 1/4 section corner of section 5 only, monumented with a red trachyte stone, 20x9x5 inches, firmly set, clearly marked 1/4 on west face. (Record; flint stone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36S
1/4 S5
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls 56.1 ft. north of a fence line extending east and west, on a steep rocky north slope in juniper growth.

S. 89°56.7' W., beginning new measurement.

37.439

True point for the closing corner of sections 31 and 32 only, T. 36 S., R. 17 W., as described in the official record of the dependent resurvey of Township 36 South, Range 17 West, surveyed concurrently under this same Group No.

41.415

The corner of sections 5 and 6 only, monumented with a red trachyte stone, 12x10x5 inches, firmly set, clearly marked 5 notches on east and 1 notch on west edges, and witnessed with a mound of stone to the north. (Record; flint stone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36S
S6|S5
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls 8.4 ft. south of a fence line extending east and west, on a gradual rocky north slope in sagebrush and juniper growth.

N. 89°44.4' W., along the north boundary of section 6.

36.364

Point for the 1/4 section corner of section 31 only, T. 36 S., R. 17 W., at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 3 inches in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, with aluminum cap marked:

T36SR17W
1/4 S31
T37S
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls 2.7 ft. south of a fence line extending east and west, on open rocky ground in juniper growth.

41.007

The 1/4 section corner of section 6 only, monumented with a trachyte stone, 12x12x4 inches, firmly set, clearly marked 1/4 on north face, and CC on south face, and witnessed with a mound of stone to the south. (Record; granite stone)

No remaining evidence of the original bearing tree was found.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36S
1/4 S6
T37SR17W
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls in a fence line extending east and west, on flat open ground in scattering juniper growth.

S. 89°49.7' W., beginning new measurement.

THE DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

40.810

The corner of Tps. 36 and 37 S., Rgs. 17 and 18 W., monumented with a red flint stone, 20x8x5 inches, firmly set, in a fence corner projecting south and east, clearly marked 6 notches on south and west edges, no other marks visible. (Record; 6 notches on north, south, east, and west edges.)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T36S
R18W R17W
S36 | S31
S1 | S6
T37S
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Corner falls on a gradual southwest slope in sagebrush and juniper growth.

From this corner, National Geodetic Survey Station "BIG MOUNTAIN" monumented with a standard disk stamped BIG MNT 1938, cemented in a sandstone outcropping, bears, S. 52°23.5' E. (FWD), N. 52°17.8' W. (REV), 849.616 chains distance.

The Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 37 S., R. 17 W., Salt Lake Meridian, Utah.

The Reestablishment of the Survey Executed by
T.C. Bailey in 1881

From the corner of sections 11, 12, 13, and 14, monumented with an iron post, 2 inches diameter, firmly set, projecting 3 inches above the ground, with brass cap marked as described in the official record of the 1911 resurvey.

Corner falls on north edge of an oiled road extending east and west.

N. 0°14.2' W., between sections 11 and 12.

41.612

Point for the 1/4 section corner of sections 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
24 inches below ground surface, with aluminum cap marked:

T37SR17W
1/4
S11|S12
2007

Deposit three magnets enclosed in plastic cases at the base of
the aluminum post.

Corner falls in an irrigated field.

- 83.224 The corner of sections 1, 2, 11, and 12, monumented with a
Washington County survey monument, an iron pipe, 2 1/2 inches
diameter, firmly set, with brass cap attached marked:

T37SR17W
|S12
1979

This monument is accepted as the best available evidence of
the position of the original section corner.

An area reference plat, dated June 1979, is on file at the
Washington County Recorder's Office.

Corner falls in the corner of fences projecting south, east,
and west, on the south edge of a dirt road extending east and
west.

From the corner of sections 1, 6, 7, and 12, on the east
boundary of the township, hereinbefore described.

N. 88°42.0' W., between sections 1 and 12.

- 40.235 The 1/4 section corner of sections 1 and 12, monumented with a
Washington County survey monument, an iron pipe, 2 inches
diameter, lying vertical, 1.5 ft. below ground surface, with
brass cap attached with no visible markings. Measure to the
base of the iron post, monument not reset. This monument is
accepted as a careful and faithful determination of the 1/4
section corner position.

An area reference plat, dated June 1979, is on file at the
Washington County Recorder's Office.

Corner falls in an irrigated field.

N. 88°43.2' W., beginning new measurement.

- 40.254 The corner of sections 1, 2, 11, and 12.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 1°13.1' W., between sections 1 and 2.

39.233 The 1/4 section corner of sections 1 and 2, monumented with a Doug Grimshaw survey monument, a rebar, 5/8 inch diameter, firmly set, with yellow cap attached, marked: Grimshaw PLS 174457. This corner is accepted as a careful and faithful determination of the 1/4 section corner position.

A record of survey plat, dated April 19, 1995, is on file at the Washington County Recorder's Office.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T37SR17W
1/4
S2|S1
2007

Deposit the rebar and cap at the base of the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls 35.6 ft. north of a fence line extending east and west, and next to a street sign reading ASGARD WAY and LEMAN WAY, on a north facing cut slope.

N. 1°13.2' W., beginning new measurement.

19.613 The N 1/16 section corner of sections 1 and 2, monumented with a Doug Grimshaw survey monument, a rebar, 5/8 inch diameter, firmly set, with yellow cap attached, marked: Grimshaw PLS 174457. This corner is accepted as a careful and faithful determination of the N 1/16 section corner position.

A record of survey plat, dated April 19, 1995, is on file at the Washington County Recorder's Office.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

N 1/16
S2|S1
2007

Deposit the rebar and cap at the base of the aluminum post.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls 1.4 ft. south of the corner of fences projecting north and west, on a gradual southeast slope.

N. 1°13.1' W., beginning new measurement.

20.010

The corner of sections 1 and 2 only, on the north boundary of the township, hereinbefore described.

The Reestablishment of the Survey Executed by
T.C. Bailey in 1881, and the Resurvey Executed by
R. Gentry and H.D. Heist in 1911.

From the corner of sections 10, 11, 14, and 15, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 2006 resurvey.

Corner falls 6 ft. east of the corner of corral fences projecting south and west, and 2 ft. west of a fence line extending north and south.

N. 0°12.1' W., between sections 10 and 11.

40.045

The 1/4 section corner of sections 10 and 11, monumented with an unrecorded rebar, 5/8 inch diameter, firmly set, with no cap attached. This corner is accepted as a careful and faithful determination of the original 1/4 section corner position, according to the official record of the 1911 resurvey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T37SR17W
1/4
S10|S11
2007

Deposit a magnet enclosed in a plastic case and rebar at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls 20 ft. north of dirt road extending N. 64° W., and S. 64° E, on flat ground in sagebrush.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

The Reestablishment of the Survey Executed by
T.C. Bailey in 1881

N. 0°52.4' W., beginning new measurement.

20.312 Point for the N 1/16 section corner of sections 10 and 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
26 inches in the ground, with aluminum cap marked:

N 1/16
S10|S11
2007

Deposit a magnet enclosed in a plastic case at the base of the
aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

40.624 Point for the corner of sections 2, 3, 10 and 11, at
proportionate distance; there is no remaining evidence of the
original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
20 inches in the ground, to solid rock, in a mound of stone, 3
ft. base, to top, with aluminum cap marked:

T37SR17W
S3|S2
S10|S11
2007

Deposit a magnet enclosed in a plastic case at the base of the
aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual southwest slope in sagebrush and in
an old chaining.

From the corner of sections 1, 2, 11, and 12.

S. 87°54.9' W., between sections 2 and 11.

40.684 Point for the 1/4 section corner of sections 2 and 11, at
proportionate distance; there is no remaining evidence of the
original corner.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T37SR17W
S2
1/4 —
S11
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls 44.6 ft. west of a fence line extending north and south, on flat ground in sagebrush and scattering juniper growth.

61.026 Point for the W 1/16 section corner of sections 2 and 11, not monumented.

81.368 The corner of sections 2, 3, 10, and 11.

N. 0°58.0' W., between sections 2 and 3.

40.622 Point for the 1/4 section corner of sections 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T37SR17W
1/4
S3 | S2
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a steep east slope in bitterbrush.

81.915 The corner of sections 2 and 3 only, on the north boundary of the township, hereinbefore described.

From the corner of sections 9, 10, 15, and 16, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 2006 resurvey, and a steel fence post alongside.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°17.2' W., between sections 9 and 10.

40.386 The 1/4 section corner of sections 9 and 10, monumented with a granite stone, 12x8x8 inches, firmly set, clearly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T37SR17W
1/4
S9|S10
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a mound of stone, 4 ft. by 3 ft. base by 1 ft. high, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual south slope in old chaining.

N. 0°12.3' E., beginning new measurement.

20.245 Point for the N 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

N 1/16
S9|S10
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in a hollow drains N. 80° E., in an old burn.

40.490 The corner of sections 3, 4, 9, and 10, monumented with a volcanic stone, 12x12x10 inches, firmly set, clearly marked 3 grooves on east and 5 grooves on south faces. (Record; 3 notches on east and 5 notches on south edges)

At the corner point

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T37SR17W
S4|S3
S9|S10
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gentle south slope.

From the corner of sections 2, 3, 10, and 11.

S. 87°34.5' W., between sections 3 and 10.

20.362 Point for the E 1/16 section corner of sections 3 and 10, not monumented.

40.724 The 1/4 section corner of sections 3 and 10, monumented with a granite stone, 14x10x8 inches, firmly set, dimly marked 1/4 on north face, and witnessed with a mound of stone to the east. (Record; lava stone)

No remaining evidence of the original bearing tree was found.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T37SR17W
S3
1/4 —
S10
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls in old chaining, on a gradual east slope in sagebrush and scattering juniper growth.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 86°51.6' W., beginning new measurement.

39.770 The corner of sections 3, 4, 9, and 10.

N. 1°52.5' W., between sections 3 and 4.

39.295 The 1/4 section corner of sections 3 and 4, monumented with a lava stone, 16x8x5 inches, firmly set, dimly marked 1/4 on west face, and witnessed with a mound of stone to the east.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T37SR17W
1/4
S4|S3
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gentle rocky south slope in old burn.

N. 1°06.3' W., beginning new measurement.

42.284 The corner of sections 3 and 4 only, on the north boundary of the township, hereinbefore described.

From the corner of sections 3, 4, 9, and 10.

N. 89°05.2' W., between sections 4 and 9.

41.072 Point for the 1/4 section corner of sections 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T37SR17W
S4
1/4 —
S9
2007

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in juniper growth.

82.144

The corner of sections 4, 5, 8, and 9, monumented with a trachyte stone, 20x8x5 inches, firmly set, clearly marked 4 notches on east and 5 notches on south edges, and witnessed with a mound of stone to the west. (Record; volcanic stone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T37SR17W
S5|S4
S8|S9
2007

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a rocky south slope in juniper growth.

N. 0°55.4' W., between sections 4 and 5.

40.152

Point for the 1/4 section corner of sections 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap marked:

T37SR17W
1/4
S5|S4
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a rocky south facing slope, 100 ft. from top of ridge, bears northwest and southeast.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

60.228

Point for the N 1/16 section corner of sections 4 and 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, to solid rock, in a mound of stone 5 ft. base, to top, with aluminum cap marked:

N 1/16
S5|S4
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a steep rocky south slope in sagebrush and juniper growth.

80.806

The corner of sections 4 and 5 only, on the north boundary of the township, hereinbefore described.

The Subdivision of Section 1,
T. 37 S., R. 17 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 1 and 12.

N. 0°37.2' W., along the N - S centerline of section 1.

39.890

Point for the center 1/4 section corner, at intersection with the E - W centerline of section 1, not monumented.

60.076

Point for the center N 1/16 section corner of section 1, not monumented.

80.464

The 1/4 section corner of section 1 only, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.

N. 89°40.1' W., along the E - W centerline of section 1.

40.513

The point for the center 1/4 section corner of section 1.

60.835

Point for the center W 1/16 section corner of section 1, not monumented.

81.157

The 1/4 section corner of sections 1 and 2.

From the point of the center W 1/16 section corner of section 1.

THE SUBDIVISION OF SECTION 1,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°54.9' W., along the N - S centerline of the NW 1/4 of section 1.

- 19.900 The NW 1/16 section corner of section 1, at intersection with the E - W centerline of the NW 1/4 of section 1, monumented with a Doug Grimshaw monument, a rebar, 5/8 inch diameter, firmly set, with cap missing. This corner is accepted as a careful and faithful determination of the NW 1/16 section corner position.

A record of survey plat, dated April 19, 1995, is on file at the Washington County Recorder's Office.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, flush with the ground, with aluminum cap marked:

NW 1/16
S1
2007

from which

A railroad tie, with a nail in it, bears N. 84° E., 49 links distance.

A power pole, with a nail in it, bears S. 10° E., 45 links distance.

Deposit the rebar at the base of the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on north edge of dirt road to the Cowley's home.

N. 0°54.9' W., beginning new measurement.

- 20.198 The W 1/16 section corner of section 1 only, on the north boundary of the township, hereinbefore described.

From the point for the center N 1/16 section corner of section 1.

S. 89°31.3' W., along the E - W centerline of the NW 1/4 of section 1.

- 20.422 The NW 1/16 section corner of section 1.

S. 89°31.3' W., beginning new measurment.

THE SUBDIVISION OF SECTION 1,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

20.419 The N 1/16 section corner of sections 1 and 2.

The Subdivision of Section 4,
T. 37 S., R. 17 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 4 and 9.

N. 1°07.3' W., along the N - S centerline of section 4.

39.712 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T37SR17W
C 1/4
S4
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a small mound of stone west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat open ground in old burn.

60.225 Point for the center N 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C
N 1/16 | S4
C
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a mound of stone, 3 ft. by 2 ft. base by 1 ft. high, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual southeast slope in old burn, at the edge of a patch of juniper growth.

81.384 The 1/4 section corner of section 4 only, on the north boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 4,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

From the 1/4 section corner of sections 3 and 4.

N. 88°28.0' W., along the E - W centerline of section 4.

40.568 The center 1/4 section corner of section 4.

81.516 The 1/4 section corner of sections 4 and 5.

From the center N 1/16 section corner of section 4.

N. 89°04.4' W., along the E - W centerline of the NW 1/4 of section 4.

40.857 The N 1/16 section corner of sections 4 and 5.

The Subdivision of Section 10,
T. 37 S., R. 17 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 10 and 15, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 2006 resurvey.

Corner falls 20 ft. north of a fence line extending east and west.

N. 0°43.1' W., along the N - S centerline of section 10.

40.212 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T37SR17W
C 1/4
S10
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual south slope in sagebrush and juniper growth.

59.514 Point for the center N 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, flush with road surface, with aluminum cap marked:

THE SUBDIVISION OF SECTION 10,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

C
N 1/16 | S10
C
2007

Deposit two magnets enclosed in plastic cases at the base of the aluminum post.

Set two steel fence posts alongside the aluminum post.

Corner falls on north side of a two track road.

78.816 The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of sections 10 and 11.

N. 89°35.3' W., along the E - W centerline of section 10.

20.414 Point for the center E 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, to solid rock, in a mound of stone 3 ft. base, to top, with aluminum cap marked:

E 1/16
C — C
S10
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush and scattering juniper growth.

40.828 The center 1/4 section corner of section 10.

81.172 The 1/4 section corner of sections 9 and 10.

From the center E 1/16 section corner of section 10.

N. 0°47.9' W., along the N - S centerline of the NE 1/4 of section 10.

19.807 Point for the NE 1/16 section corner, at intersection with the E - W centerline of the NE 1/4 of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 10,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

NE 1/16
S10
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual west slope in sagebrush.

39.614 The point for the E 1/16 section corner of sections 3 and 10.

From the N 1/16 section corner of sections 10 and 11.

S. 88°59.7' W., along the E - W centerline of the NE 1/4 of section 10.

20.381 The NE 1/16 section corner of section 10.

40.762 The center N 1/16 section corner of section 10.

From the center N 1/16 section corner of section 10.

N. 88°14.0' W., along the E - W centerline of the NW 1/4 of section 10.

40.046 The N 1/16 section corner of sections 9 and 10.

The Subdivision of Section 11,
T. 37 S., R. 17 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of section 11 and 14, monumented with a Washington County survey monument, an iron pipe, 2 inches diameter, firmly set 1 foot below road surface in a survey vault, with brass cap attached with no visible markings. This corner is accepted as a careful and faithful determination of the 1/4 section corner position.

An area reference plat, dated August 1973, is on file at the Washington County Recorder's Office.

Corner falls in an oiled road extending north and south.

N. 0°27.3' W., along the N - S centerline of section 11.

41.085 Point for the center 1/4 section corner, at intersection with the E - W centerline of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, to solid rock, with aluminum cap marked:

THE SUBDIVISION OF SECTION 11,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

T37SR17W

C 1/4

S11

2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls 51.7 ft. north of the corner of fences projecting south, east, and west, on flat ground in sagebrush.

61.644 Point for the center N 1/16 section corner of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, to solid rock, in a mound of stone 3 ft. base, to top, with aluminum cap marked:

C
N 1/16 | S11
C
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual northeast slope in sagebrush and scattering juniper growth.

82.203 The 1/4 section corner of sections 2 and 11.

From the 1/4 section corner of sections 11 and 12.

S. 88°36.4' W., along the E - W centerline of section 11.

40.518 The center 1/4 section corner of section 11.

60.707 Point for the center W 1/16 section corner of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

W 1/16
C — C
S11
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 11,
T. 37 S., R. 17 W., SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner falls 16.4 ft. north of a fence line extending east and west, on a gradual southeast slope in sagebrush and scattering juniper growth.

80.896 The 1/4 section corner of sections 10 and 11.

From the center W 1/16 section corner of section 11.

N. 0°39.8' W., along the N - S centerline of the NW 1/4 of section 11.

20.435 Point for the NW 1/16 section corner, at intersection with the E - W centerline of the NW 1/4 of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

NW 1/16
S11
2007

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

40.870 The point for the W 1/16 section corner of sections 2 and 11.

From the center N 1/16 section corner of section 11.

S. 88°15.5' W., along the E - W centerline of the NW 1/4 of section 11.

20.265 The NW 1/16 section corner of section 11.

40.530 The N 1/16 section corner of sections 10 and 11.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
C. Scott Bishop	Cadastral Surveyor
Calvert Norton	Survey Technician
Donald Johnson	Survey Technician

CERTIFICATE OF SURVEY

We, *Ronald K. Baugh, Supervisory Cadastral Surveyor* and *Jeremy D. Davis, Cadastral Surveyor*, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing the date of the 27th day of April, 2007, we have *dependently resurveyed a portion of the east boundary, the north boundary, a portion of subdivisional lines, and subdivided sections 1, 4, 10, and 11, in Township 37 South, Range 17 West, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Aug. 04, 2009
(Date)

Ronald K. Baugh
(Supervisory Cadastral Surveyor)

July 27 2009
(Date)

Jeremy D. Davis
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east boundary, the north boundary, a portion of the subdivisional lines, and the subdivision of sections 1, 4, 10, and 11, in Township 37 South, Range 17 West, Salt Lake Meridian, Utah*, executed by *Ronald K. Baugh, Supervisory Cadastral Surveyor* and *Jeremy D. Davis, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

September 3, 2009
(Date)

Daniel W. Webb
(Chief Cadastral Surveyor for Utah)